


DECLARATION OF PERFORMANCE (KERLITE 5Plus / 6Plus) No DOP005EST

1. Unique identification code of the product-type
Dry-pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$.
2. Intended use
Ceramic tiles for internal flooring and internal and external wall applications, pre-assembled on a fibreglass mesh.
3. Name and contact address of the manufacturer
COTTO D'ESTE, via Emilia Romagna 31, 41049 Sassuolo (MO) – ITALY
4. System of assessment and verification of constancy of performance of the construction products (AVCP)
System 4
5. Name and identification number of notified body, if applicable
Not applicable
6. Declared performance

| Essential characteristics | Performance | Harmonised technical specifications |
|--|-------------------------------|--|
| Reaction to fire | A2 _{fl} -s1/A2-s1,d0 |  <p>EN 14411:2012</p> |
| Release of dangerous substances | | |
| - Cadmium | NPD | |
| - Lead | NPD | |
| Breaking strength | ≥ 700 N | |
| Modulus of rupture | ≥ 35 N/mm ² | |
| Slip resistance | See Annex enclosed | |
| Tactility | NPD | |
| Adhesion resistance | | |
| - Cementitious adhesive C1 class | NPD | |
| - Cementitious adhesive C2 class | NPD | |
| Thermal shock resistance | Passed | |
| Durability | | |
| - Internal use | Passed | |
| - External use: Frost resistance | Passed | |

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3

Sassuolo, Avril 03, 2024

Signed for and on behalf of the manufacturer by



Marco Levoni, Cotto d'Este Quality Dept.



Annex to the Declaration Of Performance N. DOP005EST

| Slip resistance | | | |
|-----------------------------------|---|---------------------------------|------------------------------------|
| Series | Products | DIN EN 16165 Annex B | BCRA D.M. 236/1989 |
| Kerlite 6 Plus Allure Smooth | Calacatta Smooth; Tundra J. Smooth; Paonazetto Smooth | NPD | NPD |
| Kerlite 6 Plus Allure Touch | Orbico Touch; Riviera Touch; Alaska Touch | NPD | NPD |
| Kerlite 6 Plus Allure Glossy | Calacatta Glossy; Tundra J. Glossy; Paonazetto Glossy; Orbico Glossy; Riviera Glossy; Alaska Glossy | NPD | NPD |
| Kerlite 5 Plus Cluny | Champagne Layé, Argerot Layé | R10 | > 0,40 |
| Kerlite 5 Plus Black-White Glossy | Ultrawhite Glossy, Black Glossy | NPD | NPD |
| Kerlite 5 Plus Black-White Glossy | Ultrawhite Silk, Black Silk | NPD | NPD |
| Kerlite 5 Plus Cement Project | Color-00 Cem Color-10 Cem, Color-20 Cem, Color-30 Cem, Color-40 Cem | R9 | > 0,40 |
| Kerlite 5 Plus Cement Project | Color-10 Work, Color-20 Work, Color-30 Work | R10 | > 0,40 |
| Kerlite 5 Plus Elegance Silk | Via Condotti Silk, Via Tornabuoni Silk, Via Montenapoleone Silk, Via Farini Silk | NPD | NPD |
| Kerlite 5 Plus Exedra Glossy | Calacatta Glossy, Estremoz Glossy, Marfil Glossy, Travertino Glossy, Albis Glossy, Onyx Extra Glossy, Riverstone Glossy, Rain Grey Glossy | NPD | NPD |
| Kerlite 5 Plus Exedra Silk | Calacatta Silk, Estremoz Silk, Marfil Silk, Travertino Silk, Albis Silk, Onyx Extra Silk, Riverstone Silk, Rain Grey Silk | NPD | NPD |
| Kerlite 5 Plus Forest | Acero, Rovere, Noce, Cembro | R10 | >0,40 |
| Kerlite 5 Plus Limestone | Clay, Amber, Oyster, Slate | R10 | >0,40 |
| Kerlite 5 Plus Materica | Bianco, Cemento, Ardesia, Avorio, Tortora | R9 | >0,40 |
| Kerlite 5 Plus Metal | Corten, Iron | R9 (Corten) NPD (Iron) | >0,40 (Corten) NPD (Iron) |
| Kerlite 6 Plus Grunge | Cloud Naturale, Musk Naturale, Storm Naturale, Taupe Naturale | R10 | >0,40 |
| Kerlite 6 Plus Pietra d'Iseo | Ceppo Naturale | R10 | >0,40 |
| Kerlite 6 Plus Lithos Naturale | Moon Naturale, Stone Naturale, Desert Naturale, Carbon Naturale | R10 | >0,40 |
| Kerlite 6 Plus Lithos Soft | Moon Soft, Stone Soft, Desert Soft, Carbon Soft | NPD | NPD |
| Kerlite 6 Plus Vanity Glossy | Bianco Luce Glossy, Bianco Statuario Glossy, Dark Brown Glossy, Macchia Vecchia Glossy, Onice Royal Glossy, Pietra Grey Glossy | NPD | NPD |
| Kerlite 6 Plus Vanity Touch | Bianco Luce Touch, Bianco Statuario Touch, Dark Brown Touch, Macchia Vecchia Touch, Onice Royal Touch, Pietra Grey Touch | NPD | NPD |



COTTODESTE

EXCLUSIVE SURFACES

| Slip resistance | | | |
|------------------------------|---|---------------------------------|-------------------------------|
| Series | Products | DIN EN 16165 Annex B | BCRA D.M. 236/1989 |
| Kerlite 6 Plus Woodland Soft | Atlantic Soft, Boreal Soft, Tropical Soft, Teak Soft, Ebony Soft | R9 | >0,40 |
| Kerlite 6 Plus Woodland Wild | Arden Wild, Grove Wild, Walden Wild | R10 | >0,40 |



Via Emilia Romagna, 31 - 41049 Sassuolo (Mo) Italy - Tel +39 0536 814911 - Fax +39 0536 814921
cottodeste.it - info@cottodeste.it

PANARIAGROUP INDUSTRIE CERAMICHE S.p.A.

Sede Legale: Via Panaria Bassa, 22/a - 41043 Finale Emilia (Mo) Italy

Capitale Sociale Euro 22.677.645,50 int. vers. - Part. IVA, Cod. Fisc. e Iscr. Reg. Imp. di Modena n. 01865640369